

SWLIFT

Diesel Articulating Boom Lift



SWLIFT Intelligent Equipment Co., Ltd as the world's leading designer and manufacturer of aerial work equipment, our products can be found around the world and we do our best to support and assist our customers.

Technical Parameters

| Model | SV20D | SV24D | SV26D | SV30D | SV38D |
|---------------------------|------------------------------|--------------|--------------------------------------|--------------|--------------|
| Max Working Height | 22m | 26.2m | 28m | 32m | 40.1m |
| Max Platform Height | 20m | 24.2m | 26m | 30m | 38.1m |
| Max Spanning Height | 9.4m | 10.2m | 10.2m | 12.2m | 19.5m |
| Max Operating Radius | 12m | 15.4m | 17.28m | 20.2m | 21.6m |
| Platform Dimensions (L*W) | 1.83×0.76m | 2.44×0.91m | 2.44×0.91m | 2.44×0.91m | 2.44×0.91m |
| Machine Length (Stowed) | 8.54m | 10.65m | 11.7m | 13.1m | 14.2m |
| Machine Width (Stowed) | 2.38m | 2.48m | 2.58m | 2.49m | 2.49m |
| Machine Height (Stowed) | 2.55m | 2.85m | 2.97m | 3.22m | 3.17m |
| Wheel Base | 2.4m | 3m | 3m | 3.66m | 3.96m |
| Ground Clearance (Center) | 0.4m | 0.4m | 0.43m | 0.43m | 0.43m |
| Machine Weight | (2WD) 9380kg (4WD) 9500kg | 16300kg | (2WD) 16800kg (4WD) 17000kg | 18000kg | 24500kg |
| Load Capacity | 230kg | 230kg | 230kg | 230kg/480kg | 230kg/480kg |
| Power | 35.5kw/2400rpm | 43kw/2200rpm | 54kw/2400rpm | 54kw/2400rpm | 54kw/2400rpm |
| Control Voltage | 12V | 12V | 12V | 12V | 12V |