

SWLLIFT

Order Pickers



SWLLIFT Intelligent Equipment Co., Ltd as the world's leading designer and manufacturer of aerial work equipment, our products can be found around the world and we do our best to support and assist our customers.

Technical Parameters

| Semi-automatic Order Pickers | | | | |
|--------------------------------|----------|----------|----------|----------|
| Specification | ST2-2.7 | ST2-3.3 | ST2-4.0 | ST2-4.5 |
| Max. Platform Height(mm) | 2700 | 3300 | 4000 | 4500 |
| Max. Machine Height(mm) | 4020 | 4900 | 5400 | 6100 |
| Min Distance to the Ground(mm) | 35 | 35 | 35 | 35 |
| Max Load(kg) | 200 | 200 | 200 | 200 |
| Platform Size(mm) | 620X 600 | 630X 620 | 630X 620 | 630X 620 |
| Battery(v/Ah) | 12/120 | 12/120 | 12/120 | 12/120 |
| Charger(v/A) | 12月15日 | 12月15日 | 12月15日 | 12月15日 |
| Overall Length(mm) | 1300 | 1300 | 1300 | 1300 |
| Overall Width(mm) | 760 | 840 | 840 | 840 |
| Overall Height(mm) | 1760 | 2040 | 1810 | 1980 |
| Overall Net Weight(kg) | 290 | 350 | 410 | 450 |

| Fully Automatic Order Pickers | | | | | |
|--------------------------------|-----------|---------|---------|-------|---------|
| Specification | ST2-2.7 | ST2-3.3 | ST2-3.5 | ST2-4 | ST2-4.5 |
| Max. Platform Height(mm) | 2700 | 3000 | 3500 | 4000 | 4500 |
| Max. Machine Height(mm) | 3989 | 4439 | 5189 | 5400 | 6000 |
| Min distance to the ground(mm) | 40 | | | | |
| Max Load(kg) | 300 | | | | |
| Platform Size(mm) | 650X 690 | | | | |
| Max Driving Speed(fall)km/h | 4 | | | | |
| Max Driving Speed(rise)km/h | 1.5 | | | | |
| Min.turning Radius(mm) | 1500 | | | | |
| Max Adapted Ground Degree(%) | 15~20 | | | | |
| Driving Wheel Size(mm) | φ 230X 80 | | | | |
| Caster Size(in) | 6 | | | | |
| Driving Motor(v/kw) | 2X24/0.4 | | | | |
| Lifting Motor(v/kw) | 24/1.6 | | | | |
| Maintenance Free Battery(v/Ah) | 2X12/120 | | | | |
| Charger(v/Ah) | 24/20 | | | | |
| Overall Length(mm) | 1520 | | | | |
| Overall Width(mm) | 760 | | | | |
| Overall Height(mm) | 1710 | 1860 | 2110 | 1810 | 1990 |
| Overall Net Weight(kg) | 560 | 580 | 600 | 662 | 682 |