

Rough Terrain Forklift



SWLLIFT Intelligent Equipment Co., Ltd as the world's leading designer and manufacturer of aerial work equipment, our products can be found around the world and we do our best to support and assist our customers.

Technical Parameters

| Rough Terrain Forklift-3T | | | |
|-----------------------------------|--|-----------------------------|--|
| Model | 3T internal combustion off- road forklift | Total Weight | 4000kg |
| Dimensions | 4200*1800*2700mm | Engine power | 40KW |
| Engine model | 490 | Climbing angle | ≤38° |
| Fork length | 1220mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 3500kg | Mast front ground clearance | 250-350mm |
| Turning radius | 3500mm | Drive mode | four-wheel drive |
| Wheelbase Center Ground Clearance | 300mm | Gearbox | 265 double high and low speed torque converter |
| Axle | Heavy cast steel bridge with small wheels | Frame | 3.5mm thicker |
| Tire | Big 20.5/70 16tires | Mast width | 160mm |

| Rough Terrain Forklift-3.5T | | | |
|-----------------------------------|--|-----------------------------|--|
| Model | 3.5T internal combustion off-road forklift | Total Weight | 4200kg |
| Dimensions | 4200*1800*2700mm | engine power | 42KW |
| Engine model | 490 | climbing angle | ≤38° |
| Fork length | 1220mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 3500kg | Mast front ground clearance | 300-380mm |
| Turning radius | 3500mm | drive mode | four-wheel drive |
| Wheelbase Center Ground Clearance | 300mm | gearbox | 280 double high and low speed torque converter |
| Axle | Heavy cast steel bridge with small wheels | frame | 3.5mm thicker |
| Tire | Big 20.5/70 16tires | Mast width | 160mm |

| Rough Terrain Forklift-4T | | | |
|--------------------------------------|--|-----------------------------|--|
| Model | 4.0T internal combustion off-road forklift | Total Weight | 5000kg |
| Dimensions | 4400*1850*2800mm | Engine power | 76KW |
| Engine model | 4120 supercharged | Climbing angle | ≤38° |
| Fork length | 1520mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 4000kg | Mast front ground clearance | 300-380mm |
| Turning radius | 4500mm | Drive mode | Four-wheel drive |
| Wheelbase Center Ground Clearance | 350mm | Gearbox | 280 Double high and low speed torque converter |
| Axle | Zhonglun side bridge | frame | 3.5mm thicker |
| tire | Big 20.5/70 16 tires | Mast width | 180mm |

Technical Parameters

| Rough Terrain Forklift-5T | | | |
|--------------------------------------|--|-----------------------------|--|
| Model | 5.0T internal combustion off-road forklift | Total Weight | 5500kg |
| Dimensions | 4400*1900*2900mm | Engine power | 76KW |
| Engine model | 4120 supercharged | Climbing angle | ≤38° |
| Fork length | 1520mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 5000kg | Mast front ground clearance | 300-380mm |
| Turning radius | 4500mm | Drive mode | Four-wheel drive |
| Wheelbase Center Ground Clearance | 350mm | Gearbox | 280 Double high and low speed torque converter |
| Axle | Dalun Bridge | frame | 3.5mm thicker |
| tire | 16/70 20 tires | Mast width | 180mm |

| Rough Terrain Forklift-6T | | | |
|--------------------------------------|--|-----------------------------|--|
| Model | 6.0T Internal combustion off-road forklift | Total Weight | 5800kg |
| Dimensions | 4400*1900*2900mm | Engine power | 85KW |
| Engine model | Yuchai 4105 | Climbing angle | ≤38° |
| Fork length | 1520mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 6000kg | Mast front ground clearance | 350mm |
| Turning radius | 4500mm | drive mode | Four-wheel drive |
| Wheelbase Center Ground Clearance | 350mm | Gearbox | 280 Double high and low speed torque converter |
| Axle | Big 30 axle | frame | 3.5mm thicker |
| TTire | 16/70 20 tires | Mast width | 200mm |

| Rough Terrain Forklift-10T | | | |
|--------------------------------------|---|-----------------------------|--|
| Model | 10T Internal combustion off-road forklift | Total Weight | 7000kg |
| Dimensions | 4400*1900*2900mm | Engine power | 121KW |
| Engine model | Yuchai 4105 | Climbing angle | ≤38° |
| Fork length | 1520mm | Rated lift height | 3000- 6000mm |
| Rated Lifting Weight | 10,000kg | Mast front ground clearance | 350mm |
| Turning radius | 4500mm | drive mode | Four-wheel drive |
| Wheelbase Center Ground Clearance | 350mm | Gearbox | 280 Double high and low speed torque converter |
| Axle | Big 30 axle | frame | 3.5mm thicker |
| TTire | 16/70 20 tires | Mast width | 200mm |